



Foundation Rock Double Row

The Foundation Rock is for use in fracturable and semi-flat rock conditions. The hard-faced flight edges are tough enough to penetrate through your hardest rock conditions.

OD	APPROX OAL	TYPE	HUB OPTIONS	CTR SHAFT
18"-24"	50.5"	DC/DC	2.5 Sq-130mm	4" x 1"
30"-60"	56"	DC/DC	2.5 Sq-130mm	6" x 1"

OD	FLIGHT THK LEAD	FLIGHT THK CARRY	HOLDERS	TEETH	PILOT BIT
18"-24"	1" - A36	1" - A36	C30	C-31HD	C-31HD
30"-60"	1" - A36	1" - A36	C30	C-31HD	C-31HD

OAL WILL VARY BASED ON HUB AND PILOT.

DESCRIPTION	SUB PART NO.	APPROX LBS	S-250	S-300	S-350	S-400	130MM
18 ROCK DBL 1"	1000000					1000008	
24 ROCK DBL 1"	1000001					1000009	
30 ROCK DBL 1"	1000002					1000010	
36 ROCK DBL 1"	1000003					1000011	
42 ROCK DBL 1"	1000004					1000012	
48 ROCK DBL 1"	1000005					1000013	
54 ROCK DBL 1"	1000006					1000014	
60 ROCK DBL 1"	1000007					1000015	