

SEVERE ROCK RIPPER[®] AUGER



AUGERS | 48" OAL

42" OAL


48" OAL

2" HEX

ITEM	DIA	NO. TEETH	LBS	PN
6-SRR	6"	8		157440
9-SRR	8"	10		157441
10-SRR	10"	10		157449
12-SRR	12"	12		157443
14-SRR	14"	14		157444
16-SRR	16"	15		157445
18-SRR	18"	16		157446
20-SRR	20"	17		157447
24-SRR	24"	20		157448
30-SRR	30"	24		CALL
36-SRR	36"	26		CALL

LBS	PN
80	137950
108	137951
	CALL
135	137952
	CALL
170	137953
192	137954
220	137955
285	137956
345	137957
415	137958

PARTS | Pilot Bits



RRP 1.75 SQ

LBS | 15

PN | 137208


Use 1.75SQ Adapter PN | 137203

THE NUTS & BOLTS:

Included with the RRP 1.75 SQ Pilot.

When purchased individually, this pilot ships with four Strata[®] SR-76SW conical teeth.


Heavy-duty Rock Drilling Pilot Bit will penetrate in your hard rock drilling conditions.



RRP-API

LBS | 18

PN | 157406

PARTS | Conical Teeth



S-RL08

Standard Rock Tooth for hard rock applications

LBS | .7

PN | 850032

P-10 Pocket

.86 Shank pocket for PRL-08 and SR-76SW Conical Teeth

LBS | .8

PN | 990043



ACCESSORIES:



Soft Hammer

LBS | 3.5

PN | 137737


STRATA[®] Conical teeth are made with a fragile carbide tip. Pengo[®] strongly recommends using a Soft Hammer when installing STRATA[®] teeth.

Due to the enlarged shoulder of the SR-76SW Strata[®] Tooth, the C30 Puller is recommended to aid in removing the tooth.


C30 Puller

LBS | 3

PN | 134090



C123 Puller

LBS | 3

PN | 134091

The S-RL08 Teeth will need the C123 Puller for removal.

Strata[®] Drilling Grade Conical Teeth were developed by Pengo for the Drilling industry. They have been proven to out-perform standard rock teeth.


SR-76SW

Drilling Grade Carbide Rock Tooth provides longer tooth life in extreme hard drilling conditions

LBS | .7

PN | 850035


STRATA
DRILLING GRADE CARBIDE