

AUGER PARTS & ACCESSORIES

INSTALLATION & REMOVAL TOOLS

SOFT HAMMER

LBS | 3.5

PN | 137737



For easy installation of Fas-N-Lok® & STRATA® Conical Teeth, use a soft hammer to prevent breaking of tips.

C30 Puller

LBS | 3

PN | 134090



Due to the enlarged shoulder of the SR-76SW STRATA® Tooth, the C30 Puller is recommended to aid in removing the tooth.

C123 Puller

LBS | 3

PN | 134091



The C123 Puller is recommended to aid in removing S-RL08, P21 RR and 0.86 shank size conical teeth.

BZ-12 Puller

For Step Shank Conical Teeth

LBS | 3

PN | 850043



For ease of conical tooth removal use these designated pullers for 1" and Step Shank Conical Teeth.

DRIFT PUNCH

LBS | 1

PN | 137750



For easy removal of teeth use this drift punch.

CAST ROCK HEAD

Weld-On head for quick field repair.



The PENGU Pressure Digger Rock Augers are built with a heat-treated cast dirt head. These cast heads are high strength and low maintenance.

ITEM	DIA	# TEETH	LBS	PN
ROCK 16	16"	8	70	752800
ROCK 18	18"	9	77	752801
ROCK 20	20"	11	85	752802
ROCK 24	24"	12	102	752803
ROCK 36	36"	20	153	752805