

# AUGER PARTS & ACCESSORIES


## INSTALLATION & REMOVAL TOOLS

<b>SOFT HAMMER</b>	
<b>LBS   3.5</b>	
<b>PN   137737</b>	


For easy installation of Fas-N-Lok® & STRATA® Conical Teeth, use a soft hammer to prevent breaking of tips.

<b>C30 Puller</b>	
<b>LBS   3</b>	
<b>PN   134090</b>	


Due to the enlarged shoulder of the SR-76SW STRATA® Tooth, the C30 Puller is recommended to aid in removing the tooth.

<b>C123 Puller</b>	
<b>LBS   3</b>	
<b>PN   134091</b>	

The C123 Puller is recommended to aid in removing S-RL08, P21 RR and 0.86 shank size conical teeth.

<b>BZ-12 Puller</b>	
For Step Shank Conical Teeth	
<b>LBS   3</b>	
<b>PN   850043</b>	

For ease of conical tooth removal use these designated pullers for 1" and Step Shank Conical Teeth.

<b>DRIFT PUNCH</b>	
<b>LBS   1</b>	
<b>PN   137750</b>	

For easy removal of teeth use this drift punch.

## CAST ROCK HEAD

Weld-On head for quick field repair.



The PENGU Pressure Digger Rock Augers are built with a heat-treated cast dirt head. These cast heads are high strength and low maintenance.

ITEM	DIA	# TEETH	LBS	PN
ROCK 16	16"	8	70	752800
ROCK 18	18"	9	77	752801
ROCK 20	20"	11	85	752802
ROCK 24	24"	12	102	752803
ROCK 36	36"	20	153	752805